




E-NETTR 10/100/1000Base-T Transformer Module

P/N: H2424-R


- * Designed for long haul Gigabit Ethernet 100/1000Base-T, full duplex applications
- * Designed to meet IEEE802.3ab requirement
- * Designed to meet IR255°C peak requirement
- * Power over Ethernet (POE) Magnetics, 720mA current capability
- * Primary inductance 350uH Min with 8mA DC Bias
- * Cable interface for isolation and low common mode emissions
- * Supports 4 pairs of category 5UTP cable
- * Lead-Free & Designed to meet RoHS requirement
- * Operating temperature range -40°C to +85°C
- * Storage temperature range: -40°C to +85°C



Electrical Specifications@25°C


Part Number	Turn Ratio	Insertion Loss (dB Max)			Return Loss (dB Min)				Cross Talk (dB Min)			Hi-Pot (Vrms MIN)
		1MHz	100MHz	125MHz	30MHz	60MHz	80MHz	100MHz	30MHz	60MHz	100MHz	
H2424-R	1CT:1CT	-1.1	-1.0	-2.0	-18	-13.1	-12	-10	-40	-35	-33	1500

Mechanical



Unless otherwise specified tolerances: xx.xo ± 0.25mm
o.xx ± 0.05mm

Schematics



东莞市祥星电子有限公司

地址: 东莞市石碣镇横滘科技中路第三工业区

TEL:0769-86384669

FAX:0769-81813600

Http://www.e-nettr.com

xxing.guang@163.com