



**P/N: H2440G**

- \* Designed to meet IEEE802.3ab requirement
- \* Lead-Free & Designed to meet RoHS requirement
- \* Designed to meet IR 255°C peak Requirement.
- \* Single Port for NIC Application
- \* Operating temperature range: 0°C to +70°C
- \* Storage temperature range: 0°C to +70°C


**Electrical Specifications@25°C**

Part Number	Turn Ratio (±3%)	OCL(uH Min) @ 100KHz/0.1V	L.L (uH Max)	C <sub>w/w</sub> (pF Max)	DCR (Ω Max)	Hi-Pot (Vrms MIN)
H2440G	1CT:1CT	350	0.5	28	1.2	AC 1500/1mA

**Continue**

Part Number	Insertion Loss 0.3~100MHZ (dB Max)	Return Loss (dB Min)				Cross Talk (dB Min)		DCMR (dB Min)		
		0.3-30MHz	40MHz	50MHz	60-100MHz	30MHz	60- 100MHz	30MHz	60MHz	80-100MHz
H2440G	-1.1	-18	-14.4	-13.1	-10	-35	-32	-40	-35	-30

**Mechanical**



Unless:mm[inch] Tolerances: xx.xo± 0.25[0.010]  
o.xx± 0.05[0.002]

**Schematic**

